ELSEVIER

Volume 195, Issues 1–3, 1 January 2008

Journal of Materials Processing Technology

www.elsevier.com/locate/jmatprotec

Contents

Editorial 1
A.E. Tekkaya, J.M. Allwood

On strain localisation in tube hydroforming of aluminium extrusions 3
M. Jansson, L. Nilsson, K. Simonsson

Experimental study of Nd:YAG laser beam machining—An overview 15
A.K. Dubey, V. Yadava

Modulation of power density distribution in time and space for high speed laser cladding 27
K. Partes, G. Sepold

Determination of dielectric properties of insulator materials by means of ANFIS: A comparative study 34
M. İnal

Effective form design of electrode in electrochemical smoothing of end turning surface finishing 44
P.S. Pa

Study of fabrication of Cu film on PFA by sputtering 53
M. Matsushita, S. Aoyama

Microstructural evolution and microhardness of a melt-spun Al–6Ni–2Cu–1Si (in wt.%) alloy 58
E. Karaköse, T. Karaaslan, M. Keskin, O. Uzun

Analysis of deformations and stresses in flat rolling of wire 63
C. Vallellano, P.A. Cabanillas, F.J. García-Lomas

Micro-structural analysis of self-accommodating martensites in Cu–11.92 wt%Al–3.78 wt%Ni shape memory alloy 72
U. Sarı, İ. Aksoy

High density selective laser melting of Waspaloy® 77
K.A. Mumtaz, P. Erasenthiran, N. Hopkinson

Growth of intermetallic layer at roll bonded IF-steel/aluminum interface 88
V. Jindal, V.C. Srivastava

Automation of strip-layout design for sheet metal work on progressive die 94
S. Kumar, R. Singh

An industrial application for on-line detection of instability and wire breakage in wire EDM 101
I. Cabanes, E. Portillo, M. Marcos, J.A. Sánchez

The influence of polyethylene in the mechanical recycling of polyethylene terephtalate 110
R. Navarro, S. Ferrándiz, J. López, V.J. Seguí

Characterization of electrical contact conditions in spot welding assemblies 117
P. Rogeon, P. Carre, J. Costa, G. Sibilia, G. Saindrenan

Effects of the simultaneous imposition of electromagnetic and magnetic forces on the solidification structure of pure Al and Al–4.5 wt.%Cu alloy 125
X. Li, Z. Ren, Y. Fautrelle

Surface topography in ball end milling process: Description of a 3D surface roughness parameter 135
Y. Quinsat, L. Sabourin, C. Lartigue

Effect of additives on flexible PVC foam formation 144
H. Demir, M. Sipahioğlu, D. Balköse, S. Ülkü

(Contents continued on page I)

0924-0136(20080101)195:1/3;1-X

(Contents continued from OBC)

Laser surface treatment of electroless Ni–P coatings on Al356 alloy 154
R.S. Razavi, M. Salehi, M. Monirvaghefi, G.R. Gordani

The use of SiC powder in water as dielectric for micro-slit EDM machining 160
H.-M. Chow, L.-D. Yang, C.-T. Lin, Y.-F. Chen

Structural and electrical characteristic of crystalline barium titanate synthesized by low temperature aqueous method 171
S. Sreekantan, A.F.M. Noor, Z.A. Ahmad, R. Othman, A. West

Effect of thermal treatment on the crystal structure and morphology of zirconia nanopowders produced by three different routes 178
M.M. Rashad, H.M. Baioumy

Electro-discharge machining (EDM) versus hard turning and grinding—Comparison of residual stresses and surface integrity generated in AISI O1 tool steel 186
V. García Navas, I. Ferreres, J.A. Marañón, C. Garcia-Rosales, J. Gil Sevillano

Investigation of limiting grain size and microstructure homogeneity in the presence of second phase particles using the Monte Carlo method 195
S.M.H. Haghighat, A.K. Taheri

Investigations of tool edge radius effect in micromachining: A FEM simulation approach 204
K.S. Woon, M. Rahman, F.Z. Fang, K.S. Neo, K. Liu

Modelling of the nitriding process 212
J. Ratajski, T. Suszko

Factors affecting some quality properties of the decorative surface overlays 218
G. Nemli

Carbothermal synthesis of silicon nitride (Si_3N_4): Kinetics and diffusion mechanism 224
A. Ortega, M.D. Alcalá, C. Real

Control of energetic conditions by employing interlayer of different thickness for explosive welding of titanium/304 stainless steel 232
P. Manikandan, K. Hokamoto, M. Fujita, K. Raghukandan, R. Tomoshige

Optimization of cryogenic treatment to maximize the wear resistance of 18% Cr martensitic stainless steel by Taguchi method 241
J.D. Darwin, D. Mohan Lal, G. Nagarajan

Nitrogen spray atomization of molten tin metal: Powder morphology characteristics 248
R. Metz, C. Machado, M. Houabes, M. Elkhatib, M. Hassanzadeh

Novel mullite-based ceramics manufactured from inorganic wastes. II: Mechanical behaviour 255
F.A.C. Oliveira, V. Livramento, F. Delmas

Influence of the inaccuracy of thermal contact conductance coefficient on the weighted-mean temperature calculated for a forged blank 260
A. Polozine, L. Schaeffer

Characterization of spray lubricants for the high pressure die casting processes 267
A.S. Sabau, R.B. Dinwiddie

Hard turning of interrupted surfaces using CBN tools 275
A.E. Diniz, A.J. de Oliveira

Computational feasibility analysis of direct-adhesion polymer-to-metal hybrid technology for load-bearing body-in-white structural components 282
M. Grujicic, V. Sellappan, G. Arakere, N. Seyr, M. Erdmann

Parametric study on laser nitriding of 1.5919 steel 299
P.P. Psyllaki, A. Griniari, D.I. Pantelis

A computational model for the cooling phase of injection moulding 305
A.G. Smith, L.C. Wrobel, B.A. McCalla, P.S. Allan, P.R. Hornsby

Hybrid neural–GA model to predict and minimise flatness value of hot rolled strips 314
S. John, S. Sikdar, P.K. Swamy, S. Das, B. Maity

Direct laser fabrication of Ti6Al4V/TiB 321
F. Wang, J. Mei, X. Wu

An effect of heat input, weld atmosphere and weld cooling conditions on the resistance spot weldability of 316L austenitic stainless steel 327
B. Kocabekir, R. Kaçar, S. Gündüz, F. Hayat

Author index 336

Subject index 338